

 Schaefer  
Legend



# TRI-SEAL™

Floating Stage System

*E. J. Schaefer*

# 4" Submersible Pumps

## 4" Legend

The standard Schaefer 4" Legend submersible pump features the new TRI-SEAL floating stage system. This new stage system further improves efficiency and protects against wear when pumping abrasives (sand). All Schaefer Legend pumps are unconditionally guaranteed against sand locking in abrasive well conditions for one full year. For details on how to become a registered dealer and receive a 5 -Year warranty, contact your local distributor.


### Features

- 300 series stainless steel hub floats with the impeller maintaining a positive seal
- Phenolic washer provides downthrust protection
- Celcon®\* impeller provides high efficiency performance and abrasion resistance
- Noryl®\*\* diffuser and disc - proven abrasion resistant material
- Floating stage design allows impeller to float independently
- Removable, spring-loaded check valve
- Maximum water temperature: 120 °F
- Ceramic shaft sleeve and rubber discharge bearing protect shaft and eliminate sand wear
- Powered by Franklin Electric corrosion resistant 4" submersible motors

\* Celcon® is a registered trademark of the Celanese Corporation.

\*\* Noryl® is a registered trademark of G.E.

Patented impeller hub seal system seals radially and axially to prevent fluid recirculation, providing high performance in the harshest conditions.



CSA CERTIFIED  
PUMP END ONLY



Drinking Water  
NSF/ANSI 61



**Franklin Electric**

400 East Spring Street, Bluffton, Indiana 46714  
Tel: 260.824.2900 Fax: 260.824.2909  
www.franklin-electric.com



Ordering and performance data available online at [www.franklin-electric.com/pumps/](http://www.franklin-electric.com/pumps/)